

MU SERIES

INTELLIGENT BATTERY CHARGER

MU-1267A
MU-1277A
MU-1244A
MU-1215A
MU-1248A



MU-1230A
MU-2415A

Features:

- **Microcontroller Based**
- **Fully Automatic**
- **Adaptive Charging**
- **For Lead-Acid, Ni-Cd & Ni-MH Batteries**
- **Adjustable Charging Capacity**
- **Suitable For 1AH-300AH Batteries**
- **Short Circuit & Polarity Protections**



NEURON TECHNOLOGY LIMITED

Room 21, 8/F., Goldfield Industrial Centre, 1 Sui Wo Road, Fo Tan, Shatin, N.T. Hong Kong

Tel : (852) 2688 6400

E-mail : sales@neuron.com.hk

Web Site : www.neuron.com.hk

Fax : (852) 2688 6404

enquiry@neuron.com.hk

MU SERIES BATTERY CHARGER

FEATURES

- Microcontroller based
- Fully automatic without intervention
- Float charge for 100% re-charge capacity
- Adaptive charging condition
- Panel LED indications on charging condition
- Maintain longer battery life
- Suitable for 6V, 7.2V, 12V and 24V batteries
- Adjustable charging capacity ranging from 1Ah to 300Ah
- Short circuit and polarity reverse protections

SPECIFICATIONS

Model	MU-1267A	MU-1277A	MU-1244A	MU-1215A	MU-1248A
Input AC Voltage	110V AC / 220V AC				
Line Frequency	50Hz / 60Hz				
Charging Voltage	6V / 12V	7.2V / 12V	12V / 24V	6V / 12V	12V / 24V
Charging Capacity	1Ah – 70Ah	1Ah – 70Ah	1Ah – 40Ah	60Ah – 150Ah	40Ah – 80Ah
Charging Current	7A (Max.)	7A (Max.)	4A (Max.)	15A (Max.)	8A (Max.)
Dimensions (mm)	130 (H) x 140 (W) x 210 (D)			130 (H) x 140 (W) x 330 (D)	
Weight	3.5Kg			7Kg	

Model	MU-1230A	MU-2415A
Input AC Voltage	110V AC / 220V AC	
Line Frequency	50Hz / 60Hz	
Charging Voltage	12V	24V
Charging Capacity	60Ah – 300Ah	60Ah – 150Ah
Charging Current	30A	15A
Dimensions (mm)	135 (H) x 225 (W) x 290 (D)	
Weight	8Kg	

Neuron Technology Ltd.

Room 21, 8/F., Goldfield Industrial Centre, 1 Sui Wo Road, Fo Tan, Shatin, N.T. Hong Kong

Tel. (852) 2688 6400

Fax. (852) 2688 6404

Email: enquiry@neuron.com.hk

Home Page: <http://www.neuron.com.hk>